

Print'nGo Street ASLAN DFP 36

Directly printable floor graphics film for applications on rough floors with non-slip safety class R9

This self-adhesive white digital printing film offers ideal conditions for short-term floor graphic applications. The 125 µm thick film for rough interior and outdoor floors like asphalt is equipped with a structured surface. It is R9-certified for its DIN 51130-compliant anti-slip properties. Common large format printing systems generate an excellent, scratch-resistant print image and the film does not require an additional protective laminate.

Not only its slip-resistance, but also its direct printability and residue-free removability make this product a safe and at once efficient floor graphics solution for applications at the point of sale, in airports, train stations, shopping malls, at exhibitions etc.

For any further information please contact our technical advisory service: **+49 2204 70880**



Construction

Face film:	Plasticized PVC (monomeric softeners)	
Thickness:	~ 125 µm	
Adhesive:	Acrylic pressure sensitive adhesive	Square quantity: ~ 100 g/m ²
Release liner:	PE coated silicone cardboard (both sides)	Square weight: ~ 140 g/m ²

Characteristics

Print'nGo Print ASLAN DFP 36 is conform to the DIN 51130 standard and therefore certificated according to non-slip safety class R9 in unprinted condition.

Adhesive strength (ASTMD-903): immediately (on concrete): ~ 5 N/25 mm

Dimensional stability: applied onto aluminium after 48 hours stored at 70 °C (25 x 25 cm) max. -1.5 %

Chemical resistance: In a preece test of 24 hours the applied film is resistant to most petroleum-based oils, greases and aliphatic solvents, mild acids, alkalis and salts.

Combustibility: Applied on aluminium, the film is self-extinguishing.

Temperature: Application temperature: min. 12 °C
Service temperature range: -30 °C up to +80 °C

Durability: Up to 6 months outdoors depending on mechanical load in central-European standard climatic conditions

ASLAN, Schwarz GmbH & Co. KG
Oberauel 2 · 51491 Overath · Germany
fon +49 2204 70880 · fax +49 2204 70850
e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN[®]
EXPERTISE IN SELF-ADHESIVE FILMS

Print'nGo Street ASLAN DFP 36

Processing

Printability:	The material is printable with solvent, latex, UV curing and screen printing inks as well as third generation latex inks. In case of insufficient drying of the printing inks, the film will be sodded and the adhesive negatively affected.
Application:	<p>The surface must be free of dust, grease and oil. The size of a single motive must be at least 0.5 m². The film is only suitable for applications on rough surfaces and has to be applied with a heat gun and the ASLAN ApplicationRoll completely into the surface. The surface must have a temperature of at least 12 °C. The temperature must not drop significantly within the next 72 hours and it has to stay dry in order that the final adhesive strength is reached.</p> <p>To prevent that the film peels off at the edges rounded corners are recommended. In depressions the durability may be limited as water accumulates in these areas. Due to the wide variety of possible surfaces own live tests are mandatory. High load might destroy or detach the film. Humidity reduces the adhesive strength significantly. As most surfaces are breathable water regularly gets between film and surface. The film must not be applied onto smooth and polished surfaces because the adhesive strength will increase significantly and removability cannot be guaranteed.</p>
Removability:	Print'nGo Street ASLAN DFP 36 can be removed without problems and in one piece for up to six months. The film has to be removed slowly and carefully.
Storage Life:	Before application the film can be stored for minimum 2 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed 'hanging' racks.

State 7|2019

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

ASLAN, Schwarz GmbH & Co. KG
Oberauel 2 · 51491 Overath · Germany
fon +49 2204 70880 · fax +49 2204 70850
e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN[®]
EXPERTISE IN SELF-ADHESIVE FILMS

Papergraphics is proud to be the UK importer and distributor of the unique ASLAN self-adhesive vinyl range.

Overview

Diva Innovation Centre
Crompton Way, Crawley
West Sussex RH10 9QR

Tel: 0345 1300 662
info@paper-graphics.com
www.paper-graphics.com



papergraphics

ASLAN and Papergraphics have a long-standing partnership with combined expertise of over 100 years in developing and supplying premium large-format digital print media for print service providers (PSPs). ASLAN self-adhesive products focus on quality, creativity and application problem-solving to make printing, installing and using ASLAN self-adhesive vinyl and films easy and effective for both PSPs and their customers.

If you'd like to know more about the availability of ASLAN self-adhesive vinyl and films or would like to discuss your project's needs with one of our experts, **please call the team at Papergraphics on 0345 1300 662**
