BF PRINTGLOW

PRINT&CUT



PRODUCT DESCRIPTION

BF PRINTGLOW is a printable polyurethane film with a photoluminescent finishing designed to make the graphics details bright in the dark.

Thanks to its self-adhesive PET film carrier even very small letters and logos can be easily cut by all current cutting plotters after the printing process.

We recommend using BF MYLAR as a transfer tape and as a protection during the heat transfer.

APPLICATION STEPS

- Print do not mirror
- Cut 45° blade
- Weed excess material
- Apply BF MYLAR remove air bubbles
- Remove from liner
- Turn on your heat press heat to 145°C/295°F
- Place your graphic on the shirt
- Press it 145°C/295°F for 12 seconds
- Wait 6/7 seconds
- Remove BF MYLAR semi-hot

SIZES

H 50 cm	L	25 mt / 12,5mt / 5 mt
H 75 cm		/
H 100 cm		/
H 150 cm		/

Comply with regulation REACH n°1907/2006/EU

TECHNICAL DATA



Film: PU/polyurethane



Thickness: 140μ (±5%)



Liner: adhesive PET



Finish: opaque



Inks: solvent, eco-solvent, latex

PLOTTER SETTING



Cut settings: do not mirror



Blade: 45°



Minimum cut: 2 cm

APPLICATION



Temperature: 145°C - 295°F



Time: 12"



Liner removal: semi-hot,

wait 6/7 seconds



Pressure: medium - 3,5 bar - 50 PSI



Textile: organic, synthetic, mixed

WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature*	40°C - 104°F
Dry clean	×
Dryer	×

stTemperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev_2021/03

follow us

















Papergraphics is proud to be the UK distributor of the exceptional B-FLEX Heat Transfer Vinyl range.

Diva Innovation Centre Crompton Way, Crawley West Sussex RH10 9QR

Tel: 0845 130 0772 info@paper-graphics.com www.paper-graphics.com



Overview

We can supply B-FLEX HTV products in 500mm, 750mm and even 1000mm widths, by the linear metre or in full-length rolls, typically 25m. If you are already a customer of Papergraphics, you will find the complete B-FLEX heat transfer vinyl product listing within your online account.

If you need further information on the availability of B-FLEX vinyl or would like to open a new Papergraphics customer account to manage your orders online: please call us on 0845 1300 772