

BF PRINTFATTY BF PRINTFATTYUV

B-FLEX
HEAT TRANSFER VINYL

PRINT&CUT

PRODUCT DESCRIPTION

BF PRINTFATTY is a polyurethane heat transfer film printable with solvent, eco-solvent and latex based inks, suitable for heat transfer on any fabric. Thanks to its sticky carrier small letters and drawings can be easily cut by all current cutting plotters after the printing process. BF PRINTFATTY can be pressed on t-shirts and sportswear or uniforms for work and is ideal for small logos or drawings to add extra dimension to the garments.

BF PRINTFATTYUV is the version of the BF PRINTFATTY film compatible with UV printers. This allows the inks to dry immediately, eliminating waiting times.

APPLICATION STEPS

- Print - do not mirror
- Cut - 60° blade
- Weed excess material
- Apply BF MYLAR - remove air bubbles
- Remove from liner
- Turn on your heat press - heat to 150°C/305°F
- Place your graphic on the shirt
- Press it - 150°C/305°F for 15 seconds
- Remove BF MYLAR - hot

SIZES

H 50 cm L 10 mt / 5 mt / 2,5 mt

H 75 cm /

H 100 cm /

H 150 cm /

Oeko-Tex
Standard 100
Class I



Comply with
regulation REACH
n°1907/2006/EU

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev_2021/03

TECHNICAL DATA



Film: PU/polyurethane



Thickness: 750μ (±5%)



Liner: adhesive PET



Finish: opaque



Inks: solvent, eco-solvent, latex

PLOTTER SETTING



Cut settings: do not mirror



Blade: 60°



Minimum cut: 2 cm

APPLICATION



Temperature: 150°C - 305°F



Time: 15''



Liner removal: hot



Pressure: medium-low - 2,0 bar - 30 PSI



Textile: organic, synthetic, mixed

WASH RESISTANCE

First wash after application wait 12 hours

Max wash temperature* 40°C - 104°F

Dry clean ✗

Dryer ✗

*Temperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

follow us

HEADQUARTERS B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com

NORTH AMERICA BRANCH B-FLEX AMERICA LLC info@b-flexamerica.com | www.b-flexamerica.com

ASIA-PACIFIC BRANCH B-FLEX PACIFIC PTY LTD info@b-flexpacific.com | www.b-flexpacific.com



BF PRINTFATTY - BF PRINTFATTYUV

PRINT&CUT

- *3-D effect*
- *Suggested for fabrics with smooth surfaces*
- *Also available for UV printers*

Papergraphics is proud to be the UK distributor of the exceptional B-FLEX Heat Transfer Vinyl range.

Overview

Diva Innovation Centre
Crompton Way, Crawley
West Sussex RH10 9QR

Tel: 0845 130 0772
info@paper-graphics.com
www.paper-graphics.com



papergraphics

We can supply B-FLEX HTV products in 500mm, 750mm and even 1000mm widths, by the linear metre or in full-length rolls, typically 25m. If you are already a customer of Papergraphics, you will find the complete B-FLEX heat transfer vinyl product listing within your online account.

If you need further information on the availability of B-FLEX vinyl or would like to open a new Papergraphics customer account to manage your orders online: **please call us on 0845 1300 772**
