### **BF PRINTSU**

PRINT&CUT



#### PRODUCT DESCRIPTION

BF PRINTSU is a polyurethane sublistop and block-out film printable with all solvent, eco-solvent and latex based inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments.

BF PRINTSU is specially formulated to prevent the pigment migration from sublimation dyed textiles and keep any graphic looking bright on any kind of polyester garment! Thanks to its sticky carrier small letters and drawings can be easily cut by all current cutting plotters after the printing process.

We recommend using BF MYLAR as a transfer tape and as a protection during the heat transfer.

#### APPLICATION STEPS

- Print do not mirror
- Cut 45° blade
- Weed excess material
- Apply BF MYLAR remove air bubbles
- Remove from liner
- Turn on your heat press heat to 140°C/285°F
- Place your graphic on the shirt
- Press it 140°C/285°F for 10 seconds
- Remove BF MYLAR hot

#### **SIZES**

H 50 cm	L 25 mt / 12,5 m	t / 5 mt
H 75 cm	L 25 mt (upon re	quest)
H 100 cm	L 25 mt (upon re	quest)
H 150 cm	L 25 mt (upon re	quest)

Oeko-Tex Standard 100 Class I



Comply with regulation REACH n°1907/2006/EU

B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com

#### **TECHNICAL DATA**

Film: PU/polyurethane

Thickness: 120μ (±5%)



Liner: adhesive PET



Finish: opaque



Inks: solvent, eco-solvent, latex

#### **PLOTTER SETTING**



Cut settings: do not mirror



Blade: 45°



Minimum cut: 2 cm

#### **APPLICATION**



Temperature: 140°C - 285°F



Time: 10"



Liner removal: hot



Pressure: medium - 3,5 bar - 50 PSI



Textile: synthetic, sublimated fabrics

#### WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature*	40°C - 104°F
Dry clean	×
Dryer	×

stTemperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

#### SAFETY NOTICE

**HEADOUARTERS** 

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in Rev\_2021/03 this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

follow us















# **BF PRINTSU PRINT&CUT** TIGER Prevents the color's pigments migration from the fabric to the film's surface Washing resistant and durable

## Papergraphics is proud to be the UK distributor of the exceptional B-FLEX Heat Transfer Vinyl range.

Diva Innovation Centre Crompton Way, Crawley West Sussex RH10 9QR

Tel: 0845 130 0772 info@paper-graphics.com www.paper-graphics.com



#### Overview

We can supply B-FLEX HTV products in 500mm, 750mm and even 1000mm widths, by the linear metre or in full-length rolls, typically 25m. If you are already a customer of Papergraphics, you will find the complete B-FLEX heat transfer vinyl product listing within your online account.

If you need further information on the availability of B-FLEX vinyl or would like to open a new Papergraphics customer account to manage your orders online: **please call us on 0845 1300 772**