

PRODUCT DESCRIPTION

BF WINDSTOP is a polyurethane Heat Transfer Vinyl for application on softshell garments. Thanks to its application temperature of just 110°C, this film is perfect to decorate waterproof jackets, hats, shoes, and other synthetic fibers with graphics and logos. The film is fully opaque thanks to its built-in barrier. This allows you to print light colors on dark textiles and also prevents dye migration on sublimated garments. BF Windstop is easy to work with.

The cutting lines are highly visible which makes the weeding process simple and quick. The sticky polyester carrier allows to reposition any letter that was accidentally misplaced.

APPLICATION TECHNIQUES

- Knockout
- Layering from other series

APPLICATION STEPS

- Cut - 45° blade
- Weed excess material
- Turn on your heat press - heat to 110°C/230°F
- Place your graphic on the garment
- Press it - 110°C/230°F for 8 seconds
- Remove the liner - hot

SIZES

H 50 cm L 20 mt / 10mt / 5 mt / 1 mt

H 75 cm L 20 mt (upon request)

H 100 cm L 20 mt (upon request)

H 150 cm L 20 mt (upon request)





Comply with
regulation REACH
n°1907/2006/EU

SAFETY NOTICE



The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev_2021/03





TECHNICAL DATA

	Film: PU/polyurethane
	Thickness: 180μ (±5%)
	Liner: adhesive PET
	Finish: opaque

PLOTTER SETTING

	Cut settings: mirror
	Blade: 45°
	Minimum cut: 1 cm

APPLICATION

	Temperature: 110°C - 230°F
	Time: 8''
	Liner removal: hot
	Pressure: medium - 3,5 bar - 50 PSI
	Textile: Softshell, synthetic, treated fabrics, sublimated fabrics

WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature	40°C - 104°F
Dry clean	✗
Dryer	✗

BF WINDSTOP

COLOUR GUIDE



- Application on Softshell and technical garments
- Sublistop
- Fully opaque



BF W700A
WHITE WINDSTOP



BF W792A
GOLD WINDSTOP



BF W796A
SILVER WINDSTOP



BF WFLU020A
NEON YELLOW WINDSTOP



BF WFLU030A
NEON ORANGE WINDSTOP



BF WFLU040A
NEON PINK WINDSTOP



BF WFLU050A
NEON GREEN WINDSTOP



Papergraphics is proud to be the UK distributor of the exceptional B-FLEX Heat Transfer Vinyl range.

Overview

Diva Innovation Centre
Crompton Way, Crawley
West Sussex RH10 9QR

Tel: 0845 130 0772
info@paper-graphics.com
www.paper-graphics.com



papergraphics

We can supply B-FLEX HTV products in 500mm, 750mm and even 1000mm widths, by the linear metre or in full-length rolls, typically 25m. If you are already a customer of Papergraphics, you will find the complete B-FLEX heat transfer vinyl product listing within your online account.

If you need further information on the availability of B-FLEX vinyl or would like to open a new Papergraphics customer account to manage your orders online: **please call us on 0845 1300 772**
