

Blackboard AntiScratch ASLAN CR 62

The specially scratch-resistant blackboard film for writing with classic chalk

The self-adhesive blackboard film is ideally suited for daily changing writings such as set-menus in bars and restaurants. From offices to children rooms, every plain surface will be turned into a writable blackboard. The specially scratch-resistant surface ensures that writings can be wiped off easily without leaving behind any ghosting and shadows.

For any further information please contact our technical advisory service:
+49 (0) 2204.708-80

Construction

face-film:	PVC	
thickness:	~ 130 µm	
adhesive:	acrylic pressure adhesive	thickness: ~ 25 g/m ²
release liner:	silicone paper	square weight: ~ 63 g/m ²

Characteristics

adhesive strength: (ASTMD-903)	immediately: after 1 week:	~ 8,4 N/25 mm ~10,7 N/25 mm
dimensional stability:	applied onto acrylic glass after 24 hours at 60 °C	max. - 0,5 %
temperature:	application temperature: service temperature range:	min. 15°C -30 °C up to +80 °C
combustibility:	Stuck on aluminum, the film is self-extinguishing	
durability:	up to 2 years outdoors in Middle European climate, vertical exposure	

ASLAN, Schwarz GmbH & Co. KG

Oberauel 2 · 51491 Overath · Germany

phone +49 (0) 2204.708 80 · fax +49 (0) 2204.708 50

e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN®

EXPERTISE IN SELF-ADHESIVE FILMS

Blackboard AntiScratch ASLAN CR 62

Processing

printability:	The material is digitally printable with UV curable inks as well as screenprinting inks. After the printing process with screenprinting inks the print has to dry out for at least 48 hours.
application:	Application dry or wet. If applied wet, a possible whitening of the adhesive occurs, but will fade away after a couple of days, depending on the weather. For a wet application we recommend the transfer liquid ASLAN TL10.
storage life:	The films can be stored at least 3 years from date of production prior to application. The films must be stored at room temperature (15-25 °C) with a relative humidity of 50-60%. To avoid pressure points on the material we recommend the rolls to be stored either standing on the core or on `hanging´ racks, which are specially designed for this purpose.

State: 03|2015

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

ASLAN, Schwarz GmbH & Co. KG

Oberauel 2 · 51491 Overath · Germany

phone +49(0)2204.708 80 · **fax** +49(0)2204.708 50

e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN®

EXPERTISE IN SELF-ADHESIVE FILMS

Papergraphics is proud to be the UK importer and distributor of the unique ASLAN self-adhesive vinyl range.

Overview

Diva Innovation Centre
Crompton Way, Crawley
West Sussex RH10 9QR

Tel: 0345 1300 662
info@paper-graphics.com
www.paper-graphics.com



papergraphics

ASLAN and Papergraphics have a long-standing partnership with combined expertise of over 100 years in developing and supplying premium large-format digital print media for print service providers (PSPs). ASLAN self-adhesive products focus on quality, creativity and application problem-solving to make printing, installing and using ASLAN self-adhesive vinyl and films easy and effective for both PSPs and their customers.

If you'd like to know more about the availability of ASLAN self-adhesive vinyl and films or would like to discuss your project's needs with one of our experts, **please call the team at Papergraphics on 0345 1300 662**
