GIMME5 SPECIAL

CAD CAM



PRODUCT DESCRIPTION

GIMME5 SPECIAL is made of Polyurethane with a metallic finish. It can be heat applied on organic or synthetic fibers in just four seconds.

This product is easy to work with; the sticky polyester carrier allows for fast weeding and easy repositioning of details that might have accidentally been removed. It is also soft and comfortable to wear, even with bulky designs.

Its thickness (80 micron) and its elasticity make GIMME5 SPECIAL pleasant and soft on any garment, and ideal for multi-layer applications. GIMME5 SPECIAL can withstand wash cycles up to 60°C.

APPLICATION TECHNIQUES

- Knockout
- Multi-layer, suggested up to 5 layers
- Layering with other products

APPLICATION STEPS

- Cut 45° blade
- Weed excess material
- Turn on your heat press heat to 140°C/285°F
- Place your graphic on the garment
- Press it 140°C/285°F for 4 seconds
- Remove the liner hot

SIZES

H 50 cm	L	25 mt / 12,5mt / 5 mt / 1 mt
H 75 cm	L	25 mt (upon request)
H 100 cm	L	25 mt (upon request)
H 150 cm	L	25 mt (upon request)

Oeko-Tex Standard 100 Class I



Comply with regulation REACH n°1907/2006/EU

TECHNICAL DATA



Film: PU/polyhurethane



Thickness: 80µ (±5%)



Liner: adhesive PET



Finish: opaque

PLOTTER SETTING



Cut settings: mirror



Blade: 45°



Minimum cut: 0,1 cm

APPLICATION



Temperature: 140°C - 285°F



Time: 4"



Liner removal: hot



Pressure: medium - 3,5 bar - 50 PSI



Textile: organic, synthetic, mixed

WASH RESISTANCE

Dryer	✓
Dry clean	×
Max wash temperature	60°C - 140°F
First wash after application	wait 12 hours

SAFETY NOTICE

HEADOUARTERS

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev_2021/03

follow us













GIMME5 SPECIAL



COLOUR GUIDE



- Metallic finishing
- Application in only 4 seconds
- Easy to weed

















NTAIN B

Papergraphics is proud to be the UK distributor of the exceptional B-FLEX Heat Transfer Vinyl range.

Diva Innovation Centre Crompton Way, Crawley West Sussex RH10 9QR

Tel: 0845 130 0772 info@paper-graphics.com www.paper-graphics.com



Overview

We can supply B-FLEX HTV products in 500mm, 750mm and even 1000mm widths, by the linear metre or in full-length rolls, typically 25m. If you are already a customer of Papergraphics, you will find the complete B-FLEX heat transfer vinyl product listing within your online account.

If you need further information on the availability of B-FLEX vinyl or would like to open a new Papergraphics customer account to manage your orders online: **please call us on 0845 1300 772**