HP Latex R2000 Printer



Unprecedented quality and colours¹ on rigid up to 98 in (2.5 m), for sustained production



Achieve amazing colours on both rigid and flexible

- Get vibrant HP Latex colour gamut on rigid while preserving media gloss and feel, and prints with no smell
- One technology for the same look across rigid and flexible campaigns lets you say goodbye to print and mount.
- Durable and flexible water-based ink for high adhesion and scratch resistance with a new HP Latex Overcoat.4

Expand your offering with the glossiest white²

- Glossiest white on transparent and coloured media with high-opacity white that resists yellowing over time.²
- No waste between white jobs⁵ with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- Automatic maintenance makes white like any other colour, including automatic recirculation and nozzle checks.

Increase your productivity with smarter printing

- Meet production peaks with high-speed quality up to 13.4 indoor/24 outdoor boards/hr⁶, continuous loading.
- Advanced engineering drives high productivity with automatic maintenance, smart vacuum, and assisted loading.
- 3 years full coverage included with the price of the printer.

For more information, please visit http://www.hp.com/go/LatexR2000

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at http://www.hp.com/communities/LKC

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Most vibrant colours based on internal HP testing, January 2018 compared to leading competitive printers under €350,000. Tested in High Quality print mode on rigid (white acrylic 12-pass, 6-colour, 120%). Internal HP

testing with HP GamutViewer, Alpha Shapes = 50,000. ² Glossiest white based on internal HP testing in January, 2018 compared to the HP Scitex FB750/FB550 Printer using UV-curable ink technology. White ink measured for the level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure. High opacity and resists yellowing based on internal HP WeatherOmeter testing October, 2017 with 1 dot-per-pixel HP Latex Overcoat, on a range of rigid and flexible unlaminated substrates. Yellowing based on L* and B* of white underflood samples. White ink capability may be optional, requiring purchase of the HP White lnk Option Kit.

³ There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.
⁴ HP Latex Overcoat improves scratch resistance on low-cost prints where lamination may be impractical or too expensive. Scratch resistance based on internal HP testing in January, 2018 demonstrating equivalent scratch-resistance performance for prints produced with HP Latex Inks for the HP Latex R Printer series and HP Latex Inks for the HP Latex 1500 Printer that provide scratch resistance comparable to representative hardsolvent inks on self-adhesive vinyl and PVC banner. Estimates by HP Image Permanence Lab on a range of media. ⁵ When HP 886 White Latex Printheads are placed in the storage cassettes, no white ink is used for servicing when printheads are not in use.

⁶ Indoor High Quality mode 6-pass, 6-colour, 100%. Outdoor mode 3-pass, 6-colour, 80%.

Technical specifications

Print

Print	
Printing modes	20 m²/hr (220 ft²/hr) - Indoor High Quality (12p 120%) ¹ 46 m²/hr (496 ft²/hr) - Indoor Production (6p 110%) ¹ 88 m²/hr (948 ft²/hr) - Outdoor (3p 70%) ¹ 17 m²/hr (183 ft²/hr) - White Overflood (100%) ¹ 35 m²/hr (380 ft²/hr) - White Spot (100%) ¹
Ink types	HP Latex Inks
Ink cartridges	9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimiser, HP Latex Overcoat, white)
Cartridge size	5 L (colours, HP Latex Optimiser, HP Latex Overcoat); 3 L (white)
Printheads	8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimiser, 2 white)
Long-term print-to-print repeatability	Average \leq 1.0 dE2000, 95% of colours \leq 2 dE2000 ²
Media	
Handling	Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance
Media types	Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas
Rigid media size	Minimum 297 x 420 mm to 2500 x 1200 mm (up to 2500 x 3050 mm with two sets of original HP Latex R2000 extension tables). Maximum sheet weight 68 kg (Minimum 11.7 x 16.5 in to 98 x 47 in (up to 98 x 120 in with two sets of optional extension tables). Maximum sheet weight 150 lb)
Roll size	60.9 cm to 2.49 m (24 to 98.4 in)
Roll weight	Up to 100 kg (Up to 220 lb)
Roll diameter	Up to 25 cm (Up to 9.8 in)
Thickness	Up to 50.8 mm (Up to 2 in)
Applications	Exhibition and event graphics; Exterior signage; Interior decoration; POP/POS; Short-run packaging; Textile; Vehicle graphics
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (w x d x	h)
Printer	$5.10 \times 2.04 \times 1.75$ m (printer); $5.10 \times 3.64 \times 1.75$ m (including standard input and output tables) (201 \times 80 \times 6% in (printer); 201 \times 143 \times 69 in (including standard input and output tables))
Shipping	5.32 x 2.24 x 2.15 m (209 x 88 x 85 in)
Operating area	8.7 x 7.23 x 3 m (28.5 x 23.7 x 9.8 ft)
Weight	
Printer	1600 kg (3527 lb)
Shipping	2800 kg (6173 lb)
What's in the box	HP Latex R2000 Printer; HP Latex R Series White Upgrade Kit; HP Latex R2000 Roll Printing Kit with 98-in spindles (x2); Pneumatic gun adapter; Table top roll holders (x2); HP 886 Latex Printheads; HP Latex Printhead Cleaning Kit; Standard input and output tables; Foot switch; HP Internal Print Server and displays (x2); Printer maintenance kit; Warranty and intro docs; Installation, Operator Training and Ramp Up Training included
Environmental rang	es
Operating temperature	15 to 30°C (59 to 86°F)
Operating humidity	20 to 70% RH (non-condensing)
Power	
Consumption	10 to 12 kW (typical)
Certification	
Safety	IEC 60950-1+A1+A2 compliant; EU (LVD and MD compliant, EN60950-1, EN12100-1, EN ISO13849-1, EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC)
Electromagnetic	Compliant with Class A requirements, including: EU (EMC Directive)
Environmental	WEEE; RoHS (EU, Turkey, Ukraine); REACH; CA 65 Prop; ErP Ecodesign Directive

Ordering information

Product

Trouder	
K0Q46A	HP Latex R2000 Printer
Accessorie	5
T7V23A Y6V16A	HP Latex R2000 Extension Tables HP Latex R Series Edge Holders Kit
Original HP	printing supplies
G0Z21A G0Z22A G0Z24A G0Z00A G0Z10A G0Z10A G0Z12A G0Z12A G0Z13A G0Z14A G0Z15A G0Z16A G0Z17A	HP 886 White Latex Printhead HP 886 Optimizer Latex Printhead HP 886 Latex Printhead HP 886 Latex Printhead HP 886 Latex Printhead HP 882 5-liter What Latex Ink Cartridge HP 882 5-liter Van Latex Ink Cartridge HP 882 5-liter Yalex Latex Ink Cartridge HP 882 5-liter Yalex Latex Ink Cartridge HP 882 5-liter Hack Latex Ink Cartridge HP 882 5-liter Light Kagen Latex Ink Cartridge HP 882 5-liter Light Magenta Latex Ink Cartridge HP 882 5-liter Dight Cart Latex Ink Cartridge HP 882 5-liter Dight Cart Latex Ink Cartridge HP 882 5-liter Dight Cart Latex Ink Cartridge HP 882 5-liter Overcoat Latex Ink Cartridge
Service and	l Support

If you want to extend the support beyond what's included: HOHX4AC HP Standard Service, Maintenance and Support extension contract HOJR1AC HP Enhanced Service, Maintenance and Support extension contract

ECO highlights

- Better for print operations no hazard warning labels or HAPs, no localised ventilation
- needed¹
 Better for the end-customer, more differentiation odorless prints² go where solvent, UV
- can't Better for the environment – HP designs end-to-end sustainability into large-format •
- Printing HP Latex Inks are UL ECOLOGO® and UL GREENGUARD GOLD Certified.³ •

Please recycle large-format printing hardware and printing supplies. Find out how at our website hp.com/ecosolutions

¹ Contains no Hazardous Air Pollutants according to EPA Method 311. Localised ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Localised ventilation equipment installation is at the discretion of the customer – See the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. ² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. ³ UL ECLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see http://www.ul.com/EL). UL GREENGUARD GOLD Certification to UL 2818 demonstrates that product usage. For more information, visit http://www.ul.com/gg or http://www.ul.com/gg or http://www.greenguard.org.

¹ Print speed may vary due to the adaptive printing mechanism to avoid image quality defects. ² Reflective measurements on a 943 colour target under CIE standard illuminant DSO, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results. Delivery support services outside of the applicable HP coverage areas may be subject to travel charges, longer response times and reduced restoration or repair commitments hours (For detailed information contact your HP Sales Representative).



