## PrintSilverEtched Dryapply ASLAN DFL 302



### Printable glass decoration film with silver etched glass effect for dry application

This printable, self-adhesive glass decoration film with silver etched glass effect is ideal for creating creative designs and sight protection on any glass surface. Metallic pigments give this decorative film a special finish and high quality look. It is ideally printable with solvent, eco solvent, latex, UV-curing and screen printing inks.

The unique ASLAN Dryapply technology makes application particularly quick and easy. A special structure with extremely fine air release channels guarantees bubble-free dry application. This structure, combined with a special adhesive, allows easy repositioning during application without risk of damage (stress whitening). After application, the adhesive wets out and the adhesive strength increases, making the film ideal even for long-term applications.

For any further information please contact our technical advisory service:

+49 (0) 22 04. 7 08-80

#### Construction

face-film:

(polymeric softeners)

thickness: ~ 80 µm

adhesive: acrylic pressure sensitive adhesive

> PE-coated silicone cardboard square weight: ~ 140 g/m<sup>2</sup>

(double-sided), with structure

### Characteristics

release liner.

immediately ~ 3 N/25 mm adhesive strength. (ASTMD-903) after 1 week ~ 9 N/25 mm

dimensional stability: applied onto aluminum

after 48 hours stored at 70 °C

(25 x 25 cm) max. -0.45 %

chemical resistance: In a preece test of 24 hours, the applied film is resistant to most petroleum based oils, greases and

aliphatic solvents, mild acids, alkaline and salts.

light proofness: DIN 53 388 non-fade grade: 7-8

(wool scale)

square quantity: ~ 25 g/m<sup>2</sup>

light transmission: DIN 53 147 ~ 57 %

combustibility: Stuck on aluminum, the film is self-extinguishing.

ASLAN, Schwarz GmbH & Co. KG

Oberauel 2 · 51491 Overath · Germany phone +49(0)2204.708 80 · fax +49(0)2204.708 50

e-mail info@ASLAN-Schwarz.com









# PrintSilverEtched Dryapply ASLAN DFL 302



temperature:

application temperature: service temperature range:

min. 15°C

-30 °C up to +80 °C

minimum durability:

7 years outdoors, with vertical exposure, in central-European standard climatic conditions

### Processing

printability:

The material is printable with solvent, eco-solvent, latex, UV-curing and screen printing inks. In case of insufficient drying of the printing inks, the film will be sodded and the adhesive negatively affected.

application:

The film is to be a applied dry only.

Using a squeegee, the material is to be applied with even and firm pressure, so that the adhesive can completely reach its final adhesion. Otherwise, a detachment of the self-adhesive film from the substrate might be caused.

For the application of letterings etc. we recommend our ASLAN application tapes or our mounting film ASLAN TMO. After removing the application tape, we additionally recommend to firmly press down the edges of the film once more with a squeegee.

It must always be ensured that no water accumulates at the cutting edges of the film (e.g. in metal or plastic frameworks) and no condensation forms on glass panes onto which the films has been installed. In such cases, and when the film is applied on a freestanding glass surface, a whitening of the adhesive might occur.

storage life:

Before application, the films can be stored for minimum 2 years from date of production. The film must be stored at room temperature  $(15-25 \, ^{\circ}\text{C})$  and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed `hanging´ racks.

State: 06|2017

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

ASLAN, Schwarz GmbH & Co. KG

Oberauel 2 · 51491 Overath · Germany **phone** +49(0)2204.708 80 · **fax** +49(0)2204.708 50 **e-mail** info@ASLAN-Schwarz.com









# Papergraphics is proud to be the UK importer and distributor of the unique ASLAN self-adhesive vinyl range.

Diva Innovation Centre Crompton Way, Crawley West Sussex RH10 9QR

Tel: 0345 1300 662 info@paper-graphics.com www.paper-graphics.com



papergraphics

#### Overview

ASLAN and Papergraphics have a long-standing partnership with combined expertise of over 100 years in developing and supplying premium large-format digital print media for print service providers (PSPs). ASLAN self-adhesive products focus on quality, creativity and application problem-solving to make printing, installing and using ASLAN self-adhesive vinyl and films easy and effective for both PSPs and their customers.

If you'd like to know more about the availability of ASLAN self-adhesive vinyl and films or would like to discuss your project's needs with one of our experts, please call the team at Papergraphics on 0345 1300 662