

WrapTheHouse matt ASLAN DFP 55

Self-adhesive matt digital printing film for rough interior and exterior walls

This digital printing film for rough walls turns every plastered or brick wall into an eye-catching advertising space. A special adhesive ensures that the digital printing film can be applied on almost all rough walls. For an application time of up to 6 months it can be removed easily in one piece without leaving residues. If fully applied with heat, the film has an outdoor durability of up to three years. Therefore, the weather-proof WrapTheHouse matt ASLAN DFP 55 is ideally suited for temporary and medium-term exterior and interior applications.

Particularly for applications in places, where reflections ought to be avoided, this film provides an optimal solution. In addition, the film's finish blends well with matt colours as they are used in UV inkjet printing.

For any further information please contact our technical advisory service:
+49 (0) 2204.708-80

Construction

face-film:	plasticised PVC	
thickness:	~ 80 µm	
adhesive:	acrylic pressure sensitive adhesive	square quantity: ~ 220 g/m ²
release liner:	PE-coated silicone cardboard (both sides)	square weight: ~ 144 g/m ²
total thickness:	~ 450 µm	

Characteristics

adhesive strength: (ASTMD-903)	immediately (on tile surface)	~ 5 N/25 mm
dimensional stability:	applied onto aluminum after 48 hours stored at 70 °C (25 x 25 cm)	max. -0.45 %
chemical resistance:	In a preece test of 24 hours the applied film is resistant to most petroleum based oils, greases and aliphatic solvents, mild acids, alkalis and salts.	
light proofness:	DIN 53 388	non-fade grade: 7-8 (wool-scale)
combustibility:	Stuck on aluminum, the film is self-extinguishing.	
temperature:	application temperature: service temperature range:	min. 15°C -30 °C up to +80 °C
durability:	If fully applied with heat onto the substrate, the film has an outdoor durability of up to 3 years.	

ASLAN, Schwarz GmbH & Co. KG
Oberauel 2 · 51491 Overath · Germany
phone +49(0)2204.708 80 · **fax** +49(0)2204.708 50
e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN 
EXPERTISE IN SELF-ADHESIVE FILMS

WrapTheHouse matt ASLAN DFP 55

Processing

printability:	The material is printable with solvent, eco-solvent, latex and UV-curing as well as screen printing inks. In case of insufficient drying of the printing inks, the film will be sodded and the adhesive negatively affected.
advice:	Some printers, e.g. Mutoh Blizzard, might cause wrinkles in the material, due to its high thickness. For further information, please contact us on +49 (0) 22 04. 7 08-80.
application:	<p>The film is suitable for applications on rough surfaces only and must be applied with a heat gun and the ASLAN ApplicationRoll. The temperature of the hot air should not exceed 120 °C, since the matt level of the film's surface might be reduced.</p> <p>The surface onto which the film is to be applied must be dry and free of dust or grease. The film is to be applied dry.</p> <p>To seal the edges, a border of 10 cm all round should be treated with a heat gun and pressed firm with a cloth; the film will adapt to the substrate.</p> <p>Due to the wide variety of possible surfaces, we recommend a test application on the surface! If the film is applied onto smooth and polished surfaces, the adhesive strength will increase significantly. In this case a removability cannot be guaranteed. Stain resistant paints on rough surfaces often do not allow a good adhesion.</p>
removability:	WrapTheHouse matt ASLAN DFP 55 can be removed in one piece within six months. The exterior wall will not be damaged, if the film is removed carefully and slowly.
storage life:	Before application, the films can be stored for minimum 2 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60 %. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed `hanging´ racks.

State: 06|2018

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

ASLAN, Schwarz GmbH & Co. KG

Oberauel 2 · 51491 Overath · Germany

phone +49(0)2204.708 80 · fax +49(0)2204.708 50

e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN®

EXPERTISE IN SELF-ADHESIVE FILMS

Papergraphics is proud to be the UK importer and distributor of the unique ASLAN self-adhesive vinyl range.

Overview

Diva Innovation Centre
Crompton Way, Crawley
West Sussex RH10 9QR

Tel: 0345 1300 662
info@paper-graphics.com
www.paper-graphics.com



papergraphics

ASLAN and Papergraphics have a long-standing partnership with combined expertise of over 100 years in developing and supplying premium large-format digital print media for print service providers (PSPs). ASLAN self-adhesive products focus on quality, creativity and application problem-solving to make printing, installing and using ASLAN self-adhesive vinyl and films easy and effective for both PSPs and their customers.

If you'd like to know more about the availability of ASLAN self-adhesive vinyl and films or would like to discuss your project's needs with one of our experts, **please call the team at Papergraphics on 0345 1300 662**
